

AIVECA MF

PLOW LINE STANDARD

www.ikedamaq.com.br

AIVECA MF - 3 PM


Fixed Mounted Mouldboard Plow

The IKEDA project makes the difference


- Works at desired depth in any soil condition.
- Lateral stability (does not “pull” the tractor) and homogenous work depth.
- Perfect incorporation of the stubble.
- Two plow lines to meet the needs of the producer: “STANDARD” and “HD” for extra duty work.




Shock Control




The mouldboard comes in contact with an obstacle.



The Shock Control is activated, disengaging the mouldboard.



The mouldboard rearms automatically with the simple lifting of the implement.



Return to the normal work.



MF - 4 L

Fixed Mounted Mouldboard Plow

Model	Mouldboard	Number of Mouldboard	Cut Width	Cut Depth	Chassis Height	Security	Total Weight	Power Minimum
MF-2 L	Smooth	2	90 cm	20 to 40 cm	72 cm (free)	Bolt-Fuse	300 kg	75 hp
MF-3 L	Smooth	3	135 cm	20 to 40 cm	72 cm (free)	Bolt-Fuse	430 kg	90 hp
MF-4 L	Smooth	4	180 cm	20 to 40 cm	72 cm (free)	Bolt-Fuse	580 kg	120 hp
MF-5 L	Smooth	5	225 cm	20 to 40 cm	72 cm (free)	Bolt-Fuse	650 kg	150 hp
MF-2 P	Polyethylene	2	80 cm	20 to 40 cm	72 cm (free)	Bolt-Fuse	412 kg	85 hp
MF-3 P	Polyethylene	3	120 cm	20 to 40 cm	72 cm (free)	Bolt-Fuse	528 kg	105 hp
MF-4 P	Polyethylene	4	160 cm	20 to 40 cm	72 cm (free)	Bolt-Fuse	644 kg	140 hp
MF-5 P	Polyethylene	5	225 cm	20 to 40 cm	72 cm (free)	Bolt-Fuse	805 kg	175 hp
MF-2 LM	Smooth	2	90 cm	20 to 40 cm	72 cm (free)	Shock Control	364 kg	75 hp
MF-3 LM	Smooth	3	135 cm	20 to 40 cm	72 cm (free)	Shock Control	526 kg	90 hp
MF-4 LM	Smooth	4	180 cm	20 to 40 cm	72 cm (free)	Shock Control	708 kg	120 hp
MF-5 LM	Smooth	5	225 cm	20 to 40 cm	72 cm (free)	Shock Control	870 kg	150 hp
MF-2 PM	Polyethylene	2	80 cm	20 to 40 cm	72 cm (free)	Shock Control	476 kg	80 hp
MF-3 PM	Polyethylene	3	120 cm	20 to 40 cm	72 cm (free)	Shock Control	618 kg	105 hp
MF-4 PM	Polyethylene	4	160 cm	20 to 40 cm	72 cm (free)	Shock Control	832 kg	140 hp
MF-5 PM	Polyethylene	5	225 cm	20 to 40 cm	72 cm (free)	Shock Control	1010 kg	175 hp