

TRILLER

LINE TRILLER

www.ikedamaq.com.br



TRILLER



Kit Press (Optional)

The Triller is the first implement of the market that in a single operation performs 3 works:


- 1 - Open a groove in the soil with adjustable depth of 30 to 70 cm;
- 2 - Install hoses of up to 2" diameter in the bottom of this groove uniformly and homogeneously;
- 3 - The groove is naturally closed by the return of the distant soil;

Ideal for conduction of water for the supply of water fountain in grazing and small irrigations.

In its major work depth, it needs tractors with 75 hp, obtaining work speed of up to 5 km/h.

Its vertical rod cuts the soil and remove the groove wall laterally. This rod special design allows the hose routing in its inner part, releasing the groove bottom. The side coating of the rod wings in polyethylene UHMW makes the soil to slide with little resistance and after its passage, groove lateral walls returns, closing it immediately retaining the hose in its more profound portion.

The hose routing in the rod inner part is ensured by guide pulleys of nylon technil, installed between the two lateral wings.



The hose mend is done inside the implement with fast interruption of movement with a fast interruption of tractor movement of placement of nipple that passes through the rod inner part.

The reel is designed to receive rolls of 100 meters of length, hose with $\text{Ø } 3/4''$ of diameter of up to $\text{Ø } 1''$ of diameter.

In order to work with hoses of $\text{Ø } 1\frac{1}{2}''$ diameter and $\text{Ø } 2''$ of diameter, it is necessary to replace only the reel.

Model	Type	Safety	Weight	Work depth	Power Minimum
Triller without Kit Press Hose $3/4''$ and $1''$	Assembled	Bolt-Fuse	480 kg	20 to 70 cm	75 hp
Triller with Kit Press Hose $3/4''$ and $1''$	Assembled	Bolt-Fuse	494 kg	20 to 70 cm	75 hp
Triller without Kit Press Hose $1\frac{1}{2}''$ e $2''$	Assembled	Bolt-Fuse	512 kg	20 to 70 cm	75 hp
Triller with Kit Press Hose $1\frac{1}{2}''$ e $2''$	Assembled	Bolt-Fuse	530 kg	20 to 70 cm	75 hp
Triller without Kit Press Hose $3/4''$ to $2''$	Assembled	Bolt-Fuse	578 kg	20 to 70 cm	75 hp
Triller with Kit Press Hose $3/4''$ to $2''$	Assembled	Bolt-Fuse	611 kg	20 to 70 cm	75 hp